

RECOCHEM

Automotive Chemicals



LLL/1970/3355/3360/3371

LOCK D-ICER

Containing isopropyl alcohol, Recochem Lock De-Icer is available in a handy nozzle bottle and works quickly to thaw/release frozen locks and lubricate internal mechanisms. Suitable for automobile and any other locks and are a fast, safe and effective way to help to prevent future freezing and rusting. Lock De-Icers are safe on most exterior finishes. Avoid contact with vinyl.

| Part No. | Size |
|----------|---------------|
| LDI-35 | 30 ml |
| LDI-35C | 30 ml, carded |



UNIVERSAL GAS LINE ANTIFREEZE

Designed for use in all types of vehicles. It is as suitable for fuel injection engines as for carbureted engines and diesel engines. It can be used in cars, trucks, motorcycles and snowmobiles.

Gas line antifreeze helps to dry moisture in fuel tanks and lines and prevent lines from freezing. It also helps ensure easy starting in cold weather. This product contains methanol, and an effective bittering agent to help prevent human or animal consumption of the product.

Part No. MHG-150, 150 ml.



FUEL INJECTION GAS LINE ANTIFREEZE

Improves engine performance, assures fast starts after storage of a vehicle and removes water from fuel tanks. It helps to keep carburetors and fuel systems clean and can be used with all grades of gasoline and diesel fuel.

Fuel Injection Gas Line Antifreeze is an ethanol based product and does not contain methanol. It is recommended for cars with fuel injection systems and is also excellent for powerboats, RVs, gasoline powered lawnmowers and snowmobiles.

Part No. FIG-150, 150 ml.



TURBO POWER® EXTENDED LIFE ANTIFREEZE/COOLANT

•Extended service life - up to 5 years or 250,000 km •Compatible with other OEM and aftermarket OAT formulated long life coolants •Can be used in GM Cars and Trucks requiring Dex-Cool® •Amine, borate, nitrate, nitrite, phosphate and silicate free •Meets the following specifications: ASTM D3306, D4985, D6210, D7583; JIS K2234; DDC 93K217; Ford WSS-M97B44-D; GM 1825M, 1899M, 6277M, Heavy Truck; Nissan NES 5059 LLC; VW TL774D and 4F

Part No. EXL-3.78, 3.78 litre.

UNIVERSAL ANTIFREEZE/COOLANT

•Protects against winter freezing and summer boil over •Prevents pitting caused by cavitation and corrosion of brass, copper, solder, steel, cast iron and aluminium •Low silicate and aluminium compatible •Recommended for older model domestic and foreign cars, and light duty trucks •Recommended change interval: Up to 2 years or 80,000 km •Meets the following specifications: ASTM D3306, D4985; GM 1825M and 1899M; Chrysler MS7170; Ford ESE-M97B44-A and ESE-M97B18-C; TMC RP 302B; SAE J1034 and J1941



| Part No. | Size |
|-------------|---|
| UNI-3.78 | 3.78 litre |
| PREUNI-3.78 | 3.78 litre, 50/50 Premix |
| UNI-205 | 205 litre non-returnable drum |
| PREUNI-205 | 205 litre non-returnable drum, 50/50 Premix |

DIESEL EXTENDED LIFE ANTIFREEZE/COOLANT

•Extended service life - up to 6 years, 12,000 hours or 960,000 km •Fully formulated; DOES NOT require initial charge of SCA •Low silicate, phosphate and amine free •Meets performance requirements of CAT EC-1 •Premixed - No additional water required •Performance specifications: ASTM D-3306, D-4985, D-5345, and D-6210; ASTM D-4656 (50/50 premix automotive); ASTM D-5345 (50/50 premix diesel); Cummins Bulletin #3666132; Detroit Diesel #7SE 298 and 93K217; GM 1825M/1899M; Caterpillar EC-1; CID-A-A-52624; SAE J1034/J1941; TMC RP 329; Ford ESE-M97B44A, ESE-M97B18-C, WSS-M97B51-A1; Mack Trucks; Freightliner 48-2288D; White Star; MAN 324; Saab-Scania 6901; Perkins; Landrover; Chrysler MS-7170, MS9769; PACCAR; Volvo/GM Heavy Truck; New Holland WSN-M97B18-D; MTU MTL 5048; JIS K2234; Mercedes Benz DBL 7700; US Federal A-A-870; TMC RP329B



| Part No. | Size |
|----------------|---------------------------------------|
| GD3000-3.78 | 3.78 litre |
| GD3000-205 | 205 litre non-returnable drum |
| PREGD3000-3.78 | 3.78 litre PRE-MIX |
| PREGD3000-205 | 205 litre non-returnable drum PRE-MIX |
| PREGD3000-1000 | 1000 litre tote PRE-MIX |

TURBO POWER® HD DIESEL ANTIFREEZE/COOLANT

•Fully formulated; DOES NOT require initial charge of SCA •Low silicate, phosphate and amine free •Prevents corrosion of brass, copper, solder, steel, cast iron and aluminium •Meets the following specifications: ASTM D3306, D4985, D6210; TMC RP 3298; DDC 7SE298, 93K217; Freightliner 48-22880; GM 1825M, 1899M, and Heavy Truck



| Part No. | Size |
|-------------|---|
| FFD-3.78 | 3.78 litre |
| PREFFD-3.78 | 3.78 litre, 50/50 Premix |
| FFD-205 | 205 litre non-returnable drum |
| PREFFD-205 | 205 litre non-returnable drum, 50/50 Premix |

TURBO POWER® GLOBAL EXTENDED LIFE ANTIFREEZE/COOLANT

•Recommended for use in all makes and models of foreign and domestic passenger vehicles and light duty trucks •Protects coolant system metals such as brass, copper, solder, steel, cast iron and aluminium •Add as a top-up to any colour antifreeze •Guarantee: Up to 5 years or 250,000 km protection •Meets the following specifications: ASTM D3306; JIS K2234



| Part No. | Size |
|-------------|-------------------------|
| GXL-3.78 | 3.78 litre |
| PREGXL-3.78 | 3.78 litre 50/50 Premix |

TURBO POWER® HD MIXED FLEET ELC ANTIFREEZE/COOLANT

•Complete Mixed Fleet use; heavy duty diesel, light truck and automotive •Borate, nitrite, amine and phosphate free •Compatible with ALL engine coolant technologies •Extended Service Life: Up to 5 years or 250,000 km (automotive); Up to 6 years or 960,000 km (heavy duty diesel) •Meets the performance requirements of: ASTM D3306, D4985, D6210-10, D7583; AS.NZ 2108.1:1997 Type A; BS 6580; GM 1825M, 1899M; DDC 93K217; JIS K2234



| Part No. | Size |
|--------------|---|
| HDMF-3.78 | 3.78 litre |
| HDMF-205 | 205 litre non-returnable drum |
| PREHDMF-3.78 | 3.78 litre, 50/50 Premix |
| PREHDMF-205 | 205 litre non-returnable drum, 50/50 Premix |